


Silt Fence on Wire Specification



Wire Mesh	
Wire Mesh	Hot-dipped Galvanized Welded
	16GA 4"x4" Hole size
Height	24" wire on 36" fabric & 36" wire on 48" fabric available
Roll Length	100'

Silt Fence Fabric		
Weight	100 Gram	
Weave	11x11 Weave	
Grab Tensile	ASTM D4632	135 x 135
Grab Elongation	ASTM D4632	15%
Mullen Burst	ASTM D3786	200 psi
Puncture	ASTM D4833	325 lbs
Trapezoid Tear	ASTM D4533	60 lbs
AOS	ASTM D4751	30 sieve
Flow Rate	ASTM D 4491	10 / gal / min / ft
Permittivity	ASTM D 4491	0.1 sec
UV Resistance	ASTM D 4355	80% @ 500 hrs

Approximate Shipping Weight/Dimensions		
	24" Wire on 36" Fabric	36" Wire on 48" Fabric
Rolls per Pallet	68	60
Pallet Size	48"x40"x96"	48"x40"x98"
Pallet Weight	1200 lbs	1200 lbs

The information contained herein is furnished without charge or obligation and the recipient assumes all responsibility for its use. Because conditions of use and handling may vary and are beyond our control, we make no representation about, and are not responsible or liable for the accuracy and reliability of said information or the performance of any product. Any specification, property or application listed herein are provided as information only and in no way modify, amend, enlarge, or create any warranty. Nothing contained herein is to be construed as permission or as a recommendation to infringe any patent.